

A770 Specifications

▲ A770 Key Specifications

A770 T4

Horsepower

68.6 kw

Rated Operating Capacity (SAE)

1508 kg

Operating Weight

4365 kg

Auxiliary Std Flow

87.1 l/min

Auxiliary High Flow

138.5 l/min

▼ Engine

A770 T4

Horsepower

68.6 kw

▼ Performance

A770 T4

Rated Operating Capacity (SAE)

1508 kg

Tipping Load

3016 kg

Operating Weight

4365 kg

Travel Speed (2-speed option)

19.8 kmh

Travel Speed

11.4 kmh

▼ Capacities

A770 T4

Fuel Tank

90.5 l

Engine Oil with Filter

12.6 l

Hydraulic Reservoir

9.5 l

Transmission (Final Drive)

41.6 l

▼ Hydraulic System

A770 T4

System Relief @ Quick Couplers

24200 kPa

Auxiliary Std Flow

87.1 l/min

Auxiliary High Flow

138.5 l/min

▼ Dimensions

A770 T4

Length

3597 mm

Length with Standard Bucket

3597 mm

Length without Attachment

2903 mm

Width

1897 mm

Width (with bucket)

1880 mm

Height with Operator Cab

2065 mm

Height to Bucket Hinge Pin

3338 mm

Reach @ Maximum Height

800 mm

Height

2065 mm

Dump Angle @ Maximum Height

37 deg

Max Dump Height

2649 mm

Turning Radius

2179 mm

Turning Radius (AWS Mode)

3848 mm

Wheelbase

1227 mm

▼ Features

A770 T4

Joystick Control

Standard

Front and Rear Work Lights

Standard

Air Conditioning

Standard

Adjustable Seat

Standard

Backup Alarm

Standard

BICS System (Interlock)

Standard

Cab Enclosure

Standard

ROPS/FOPS Approved

Standard

Sound Option

Optional

Cab Heater

Standard

Heater Air Conditioning

Standard

Operating Lights

Standard

Work Lights

Standard

Rear Window

Standard

Top Window

Standard

Seat Belt

Standard

Seat Bar

Standard

Suspension Seat

Standard

Two Speed Travel

Standard

Deluxe Instrumentation

Optional

Engine Shutdown

Standard

Hydraulic Bucket Positioning

Optional

High Flow Option

Optional

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Bob-Tach Attachment System

Standard

Tires-Ply Rating

12 PLY

Heavy-Duty Float Tires

Optional

Power Bob-Tach

Standard

Ride Control

Optional

Horn

Standard